



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

SECTION 1: Identification

1.1 Product identifier

Trade name SPIRALZ REFILL NEUTRAL ORKIN

Alternative number(s) SPZ-NEUTRAL-ORK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

ORKIN 5840 FALBOURNE STREET MISSISSAUGA , ON L5R 4B5 1-905-761-0041

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard statement
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS07, GHS08



- Hazard statements

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

United States: en Page: 1 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

- Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of water. P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to industrial combustion plant.

2.3 Other hazards

This material is combustible, but will not ignite readily.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

IUPAC name	Identifier	Wt%	Classification acc. to GHS
1,4-bis(propan-2-yl)benzene; 7,7-dimethylhexa- decane; octadecane	CAS No 64742-47-8	50 - < 75	Asp. Tox. 1 / H304 Flam. Liq. 4 / H227
1,3-diethyl propanedioate	CAS No 105-53-3	25 - < 50	Flam. Liq. 4 / H227
2-[(1-methoxypropan-2-yl)oxy]propan-1-ol	CAS No 34590-94-8	1-<5	Flam. Liq. 4 / H227
octan-3-ol	CAS No 112-14-1 589-98-0	1-<5	Flam. Liq. 4 / H227
(4R)-1-methyl-4-(prop-1-en-2-yl)cyclohex-1-ene	CAS No 5989-27-5	<1	Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Flam. Liq. 3 / H226

For full text of abbreviations: see SECTION 16.

United States: en Page: 2 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

United States: en Page: 3 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

United States: en Page: 4 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of sub- stance	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	2,6-di-tert-butyl-4- methylphenol	128-37-0	PEL (CA)		10						Cal/ OSHA PEL
US	2,6-di-tert-butyl-4- methylphenol	128-37-0	REL		10 (10 h)						NIOSH REL
US	2,6-di-tert-butyl-4- methylphenol	128-37-0	TLV®		2					iv	ACGIH® 2019
US	2-[(1-methoxypro- pan-2-yl)oxy]pro- pan-1-ol	34590-94-8	TLV®	100		150					ACGIH® 2019
US	2-[(1-methoxypro- pan-2-yl)oxy]pro- pan-1-ol	34590-94-8	PEL (CA)	100	600	150	900				Cal/ OSHA PEL
US	2-[(1-methoxypro- pan-2-yl)oxy]pro- pan-1-ol	34590-94-8	REL	100 (10 h)	600 (10 h)	150	900				NIOSH REL
US	2-[(1-methoxypro- pan-2-yl)oxy]pro- pan-1-ol	34590-94-8	PEL	100	600						29 CFR 1910.100 0

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

inhalable fraction and vapor

United States: en Page: 5 / 15

ORKIN

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)
TWA time-weighted average (long

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

weighted average (unless otherwise specified

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	various
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥294.8 °F at 101.3 kPa

United States: en Page: 6 / 15



9.2

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

number: GHS 1.0	Date of compilation: 2020-12-31
Flash point	170 °F
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	
- Lower explosion limit (LEL)	1.1 vol%
- Upper explosion limit (UEL)	14 vol%
Vapor pressure	≤3.7 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	404.6 °F (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
Other information	
Solvent content	96.15 %
Solid content	3.846 %
Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200°C)

United States: en Page: 7 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

United States: en Page: 8 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

United States: en Page: 9 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

-					_			
Ľ	Е	CI	OΝ	J 14:	Trans	port	ıntor	mation

14.1 UN number 3082

14.2 UN proper shipping name Environmentally hazardous substance, liquid, n.o.s.

Technical name (hazardous ingredients)

BUTYL HYDROXYTOLUENE BHT, MUSK G CONCEN-

TRATE

14.3 Transport hazard class(es)

Class 9 (environmentally hazardous)

14.4 Packing group III (substance presenting low danger)

14.5 Environmental hazards hazardous to the aquatic environment

Environmentally hazardous substance (aquatic BUTYL HYDROXYTOLUENE BHT, MUSK G CONCEN-

environment) TRATE

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

- Particulars in the shipper's declaration UN3082, Environmentally hazardous substance, li-

quid, n.o.s., (contains: BUTYL HYDROXYTOLUENE

BHT, MUSK G CONCENTRATE), 9, III

Class

Packing group III

Danger label(s) 9, fish and tree



Environmental hazards yes (hazardous to the aquatic environment)

Special provisions (SP)

8, 146, 173, 335, IB3, T4, TP1, TP29

ERG No 171

United States: en Page: 10 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

International Maritime Dangerous Goods Code (IMDG)

UN number 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LI-

QUID, N.O.S.

Class 9

Marine pollutant yes (hazardous to the aquatic environment)

Packing group III

Danger label(s) 9, fish and tree



Special provisions (SP) 274, 335, 969

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
EmS F-A, S-F

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

Class 9

Environmental hazards yes (hazardous to the aquatic environment)

Packing group III

Danger label(s) 9, fish and tree



Special provisions (SP) A97, A158, A197

Excepted quantities (EQ) E1
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

United States: en Page: 11 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

- Specific Toxic Chemical Listings (EPCRA Section 313) none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
(4R)-1-methyl-4-(prop-1-en-2-yl)cyclohex-1-ene	5989-27-5		EU Fragrance Allergens

- Toxic or Hazardous Substance List (MA-TURA) none of the ingredients are listed
- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
GLYCOL ETHER DPM	34590-94-8	A, O	

Legend

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part

O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
1,3-diethyl propanedioate	105-53-3		F2
(4R)-1-methyl-4-(prop-1-en-2-yl)cyclohex-1-ene	138-86-3		F2
2-[(1-methoxypropan-2-yl)oxy]propan-1-ol	34590-94-8		F2

Legend

F2 Flammable - Second Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
PROPANOL, (2-METHOXYMETHYLETHOXY)-	34590-94-8	
ACETIC ACID, OCTYL ESTER	112-14-1	

United States: en Page: 12 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
GLYCOL ETHER DPM	34590-94-8	Т

Legend

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temper- atures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temper- atures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

United States: en Page: 13 / 15





acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Asp. Tox.	Aspiration hazard
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
IUPAC	International Union of Pure and Applied Chemistry
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)

United States: en Page: 14 / 15



acc. to 29 CFR 1910.1200 App D

SPIRALZ REFILL NEUTRAL ORKIN

Version number: GHS 1.0 Date of compilation: 2020-12-31

Abbr.	Descriptions of used abbreviations
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 15 / 15